

Grand Theatre Lighting specification

Desk ETC Congo,
This will replay a Strand 500 series show disk.

Dimmers 216 ways Avolites Art 4000. (socapex out).
We do not have 5kw dimmers.

Lanterns – Stage

Selecon 38 1.2kw fresnels
Selecon 10 2.5kw fresnels
Selecon 12 28-52 1.2kw profiles.(A size gobo)
Selecon 5 4cell flood units.
Selecon 8 1cell flood units. (colour best cut onsite for floods).
Thomas 36 Parcans (CP62).
Thomas 6 Floor parcan.(CP62).

Lanterns – Front Of House

CCT 20 15-32 1.2kw Profiles (A size gobo) gallery bar.
Thomas 6 way parcan bar (CP62),1 per side upper circle.
Space for three profiles per side upper circle.
Selecon 2 x follow spots 1.2kw MSR lamps, 6way colour mag.
Colour best cut on site for spots.

Tri-lite truss vertical on each side of proscenium opening.
Access via scaffolding tower only. (we keep onsite).

We keep very little rigging equipment (scaff etc) if you need vertical booms or bars to run up /down the stage, please bring it.

Power

250A 3p power located down stage left, we keep a set of ‘powerlocks’.
We also have ‘powerlocks to camloc’ converters.

Small power distribution panel located DSL.

1	63A 1p outlet.	
1	63A 3p outlet.	These use BS4343/EN60309 (ceeform) connectors. 3p supplies utilise 5 pole connectors.
1	32A 1p outlet.	
1	32A 3p outlet.	
1	16A 1p outlet.	
1	16A 3p outlet.	

Sound equipment power is separate to the above.

